



## See instantly.

### Design features

- Designed for small meeting rooms and executive offices in Cisco CallManager environments
- Completely integrated system including camera, 12.1" LCD screen, speakers, microphone and cables
- Ultra thin portable frame with optional wall bracket

### Application features

- Delivers the ultimate visual communication experience, with business quality audio and video
- Full range of Cisco IP telephony functions, including Directory, Voice Mail and Call Control, as supported by Cisco CallManager
- Software upgradeable, to grow with the capabilities of Cisco CallManager
- Supports XML applications which deliver a range of information services to the desktop
- Interoperable with H.323 video conferencing, using Cisco CallManager
- Interoperable with H.320 (ISDN) video conferencing, using an H.323/H.320 video gateway and Cisco CallManager

### Performance features


- Bandwidth up to 768 kbps
- PC card slot for wireless LAN connection



Small footprint and slim design allow for maximum adaptability.



Use Cisco telephony services for desktop visual communications.



The TANDBERG 1000 for Cisco CallManager is ideal for executive offices and small meeting rooms.

The TANDBERG 1000 for Cisco CallManager provides the ultimate visual communications experience as a fully integrated part of the Cisco IP telephony environment. The features of Cisco CallManager, such as forward, transfer and hold work using the video system soft keys. Making or receiving a video call with the TANDBERG 1000 for Cisco CallManager is not just as easy as a phone call — it is a phone call.

**SYSTEM COMPONENTS**

Wireless remote control, built-in camera, microphone, speakers, cables, 12.1" LCD screen, table-top stand and optional wall mount bracket

**LCD SCREEN**

Wide view angle screen  
SVGA resolution  
Auto or manual brightness

**BANDWIDTH**

Cisco SCCP up to 768 kbps

**VIDEO STANDARDS**

H.261, H.263

**VIDEO FEATURES**

Picture in Picture (PIP)

**VIDEO INPUTS (1 INPUT)**

Built-in main camera  
1 x RCA / Phono, composite: document camera / auxiliary

**VIDEO FORMAT**

NTSC, PAL

**LIVE VIDEO RESOLUTIONS**

CIF (352 x 288 pixels)  
SIF (352 x 240 pixels)

**AUDIO STANDARDS**

G.711

**AUDIO FEATURES**

Automatic noise reduction  
Acoustic echo canceller  
Automatic gain control

**PRIVACY FEATURE**

Headset, 2.5 mm mini jack

**FRAME RATES**

15 frames per second 56 – 128 kbps  
30 frames per second 168 – 768 kbps

**NETWORK**

Requires CallManager version 4.0 or newer  
Network features as supported by Cisco SCCP and Cisco CallManager  
Interoperability with H.323 and H.320 through Cisco CallManager

**CALL CONTROL**

Includes Cisco SCCP functions such as call waiting, call forwarding, call transfer to voice and video IP phones, call hold, call monitoring, call park, call back, call join, call pickup

**WIRELESS LAN SUPPORT**

Compliant with IEEE 802.11b, up to 11 Mbit  
Support for 64 / 128 bit encryption (WEP)  
Infrastructure or ad-hoc mode

**ETHERNET / INTERNET / INTRANET CONNECTIVITY**

TCP/IP, DHCP, ARP, FTP, Telnet, TFTP, DNS  
Wired 10/100 Mbit full / half duplex (manual or auto detect selection)

**CAMERA**

1.7 x zoom  
1/3" CCD  
+5° / -20° tilt (mechanical)  
47° vertical field of view  
65° horizontal field of view  
450 (PAL) / 460 (NTSC) horizontal TV lines  
Min. illumination 0.5 Lux (F1.4)  
Manual focus  
Auto or manual brightness and white balance  
15 near and far-end camera pre-sets

**DIRECTORY SERVICES**

Missed calls list  
Received calls list  
Placed calls list  
Shared and personal directory  
Advanced directory search

**POWER**

Auto-sensing power supply  
100 – 250 VAC, 50 – 60 Hz  
45 watts max.

**UNIT DIMENSIONS**

Height: 17.7" / 45.0cm  
Width: 11.8" / 30.0cm  
Depth: 2.6" / 6.6cm  
Weight: 9.0lbs / 4.1kg

*All specifications subject to change without notice.*

*Cisco is a registered trademark of Cisco Systems, Inc. and/or its affiliates in the U.S. and certain other countries.*

*TANDBERG and Real Communication Experience are registered trademarks or trademarks of TANDBERG and/or its affiliates in the U.S. and certain other countries.*